

Lane/3600

Fast, secure and compact PIN Pad solution



- Ensure best-in-class transaction ease with a clearly marked contactless zone
- The compact size and wide range of mounting accessories allow for easy integration into your retail environment
- The user friendly and intuitive terminal allows for easy integration with self checkout and kiosk solutions



ingenico



The Lane/3600's compact design allows it to fit perfectly in any retail or hospitality environment.



Optimized for payment

All payment methods accepted, with an easy to identify contactless reader.

- Designed for intensive use cases in retail
- Powerful processing to increase transaction speed
- Boosted memory (Up to 512MB RAM 512MB FLASH)
- High speed processor (Cortex A7)

Robust device for demanding retail environment

- Display with glass lens
- High-performance swipe and card insertion.

Easy integration into semi-attended kiosks

Optional kiosk adaption plate provides optimized installation.

Optional integrated rear camera/QR code reader

- Full-integrated 0.3MP rear camera

Highest security

- PCI PTS v6
- Anti-theft Kensington lock receptacle



Processor	• Application & Crypto processor	• Cortex A7	✓
Memory	• Internal	• 256 MB Flash, 256 MB RAM • 512 MB Flash, 512 MB RAM	✓ Optional
OS		• Telium TETRA	✓
SAM	• SAM slots	• 1	✓
Card Reader(s)	• Magnetic card reader • Smart Card • Contactless	• ISO 1/2/3, 500k reads lifespan bi-directional swiping • L1, 500k reads lifespan • EMV Contactless L1 3.0 spec compliant	✓ ✓ ✓
Integrated Camera		• .3 MegaPixels (QR code library embedded)	Optional
Display		• 2.8" backlight, glass lens, QVGA (320x240 pixels)	✓
Touchscreen	• Capacitive	• Finger, 1 million lifespan signature	Optional
Keypad	• Physical keys	• 15 keys, raised markings, backlit • 4 function keys • Laser etched	✓ ✓ ✓
Audio	• Buzzer • Audio Jack • Speaker	• Stereo • Mono	✓ Optional

Terminal Connections	• HDMI	• IDMI	✓
Terminal Connections via Accessories	• Ethernet • USB	• Ethernet 10/100 base T • USB Host • USB Slave • 1 x RS232 • 5V & 12V (USB retail) • 12 V	✓ ✓ ✓ ✓ Optional Optional Optional
Stand Mounting	• Universal Payment Mount		Optional
Kiosk Mounting		• Kiosk adaption plate	Optional
ADA Features		• Raised markings, backlit and 5 key dimple for orientation	✓
Terminal Size	• Terminal full option	• 6.54x3.18x1.57" (166.7 x 81.6 x 40.4 mm)	✓
Terminal Weight		• 8oz (227g)	✓
Environment	• Operating temperature • Storage temperature • Relative humidity	• 32°F to 122°F (0 to +50°C) • -4°F to 131°F (-20 to +70°C) • 104°F (85% HR at +40°C)	✓ ✓ ✓
Security	• PCI PTS • Anti-theft	• PCI PTS V6 compliant • Kensington lock receptacle	✓ ✓



www.ingenico.com

ingenico