

# SUNMI P2 SMARTPAD Payment Terminal New

Integrated PINpad for a faster checkout experience

## High Performance For Seamless Payment

Built-in quad-core 1.3GHz processor and large memory optional ensure smooth operation. PCI PTS 6.x certified, the P2 SMARTPAD satisfies local payment compliance, for your every transaction to be secured.

## Ergonomic Design Powering A High-end User Experience

P2 SMARTPAD presents a large 4" landscape mode screen to provide users a wider interface. The ergonomic keypad is designed to facilitate reliable and accurate input. IP53 rated, the P2 SMARTPAD can sustain liquid spilling or splashing.

## Multi-option Payment Support

Accepting any electronic payment method, including Chip & Pin, Chip & Sign, Magstripe, QR code, Contactless, Google pay/Apple pay, P2 SMARTPAD fulfills your customers payment needs.

## SUNMI OS Empowers Better Operational Efficiency

During payment, kiosk mode can effectively prevent any program exit caused by user misuse. Default application startup can be set on SUNMI Partner Platform for P2 SMARTPAD to boot directly on a selected application.



## P2 SMARTPAD Tech Specs

<b>Model Approved</b> T6A10	<b>OS</b> SUNMI OS (*based on Android 9.0)	<b>Processor</b> Cortex-A53, quad-core 1.3GHz	<b>Memory</b> 1GB RAM+8GB Flash; 2GB RAM+16GB Flash (optional)	<b>Display</b> 4" color screen, WVGA; 480*800; Capacitive multi-touch
<b>Camera</b> Front: 0.3MP, FF 1D/2D barcode scanning 5MP, FF (optional) Photo-taking supported	<b>NFC Reader</b> Type A&B card, MIFARE card; ISO/IEC 14443, qUICS, PayPass, payWave	<b>Magstripe Reader</b> 1/2/3 track; Bi-directional card reading; ISO 7810/7811 compliant	<b>IC Card Reader</b> Smart IC card; ISO 7816/EMV compliant	<b>PSAM Card Slot</b> 2*PSAM
<b>Micro SD Card Slot</b> 1*Micro SD (up to 32GB)	<b>Speaker</b> 1*1W	<b>MIC (Optional)</b> 1*MIC	<b>Wi-Fi</b> 2.4GHz/5GHz IEEE 802.11 a/b/g/n/ac	<b>Bluetooth</b> Bluetooth 4.1, BLE
<b>Keyboard</b> 15 keys (10 numeric keys+5 function keys); raised markings Backlit supported	<b>Ports</b> 1*RJ45 LAN port, 1*Type-C support RS232, USB 1*Audio jack 1*Kensington	<b>LAN</b> LAN 10/100Mbps	<b>Power Adapter</b> Input: AC 100~240V Output: DC 12V/1A PoE, Powered USB, Powered RS232 supported	<b>Dimensions (L*W*H)</b> 181.85*117.8*54.5mm
<b>Total Weight</b> 385g	<b>Protection</b> IP53	<b>Environment</b> Operating temp: -10°C~50°C Storage temp: -20°C~70°C	<b>Accessories (Optional)</b> Stylus Pen, Rotatable Mount, Customizable Multi-function Cable	<b>Security</b> PCI PTS 6.x